

Technical Data touchTymp MI 24

TYMPANOMETRY

Probe Frequency	226 Hz , 85 dB SPL
Optional High Frequency	1000 Hz, 69 dB SPL
Pressure Range	-600 to +400 daPa
Volume Range	0.0 ml to 6.0 ml (compensated)
Compliance Range	0.1 ml to 8.0 ml at 226 Hz 0.1 to 15.0 mmho at 1000 Hz (option)
Test Time	3 - 5 seconds
Features	RaceCar, YBG components, Compensated and uncompensated

STANDARDS

Tympanometer	IEC 60645-5, Type 2
Safety	IEC 60601-1, Class I, Type B Applied Parts
EMC	IEC 60601-1-2
CE 0123	Class IIa according to Medical Device Regulation (EU) 2017/745

ACOUSTIC REFLEXES

Test Frequencies	500, 1000, 2000, 4000 Hz
Test Methods	Ipsilateral; optional contralateral
Level Ipsilateral	70 dB HL to 105 dB HL
Level Contralateral	70 dB HL to 120 dB HL
Level Setting	Automatic, fixed
Features	RaceCar, AGC ipsilateral, Steady and pulse signal

Specifications are subject to change without notice.

DEVICE GENERAL

Display	10.4" Graphic LED-Display with resistive touch screen
PC Interface	USB
Probe	Lightweight hand-held probe with built-in control light and switch
Printer	Fast 4" thermal printer
Power Supply	Mains 100 to 240 V~, 50 - 60 Hz
Dimensions	W x D x H: 30 cm x 34.5 cm x 14.8 cm
Weight	3.2 kg
Languages	English, Chinese, French, German, Italian, Polish, Russian, Swedish, Spanish, Turkish